

GENERAL SPECIFICATIONS

Throat Diameter	1" - 25 mm	
Nominal Impedance	8 Ohm	
Power handling (AES) (*)	20 Watt	
Max Power	40 Watt	
Minimum Impedance	6,5 Ohm	±0,7 Ohm
Frequency Range	2 - 20 kHz	
Voice coil resistance	6,5 Ohm	±0,4 Ohm
Voice Coil Diameter	26 mm	1 in
S.P.L. (1w, 1m)	103 dB	±1,5 dB
Nominal Fs	2500 Hz	±200 Hz
Flux Density	2 T	±0,1 T
Crossover Frequency	2 kHz	12 dB/oct

(*) Life Test

<i>Input Signal</i>	<i>Pink noise</i>
<i>Band Pass Filter</i>	<i>3-20kHz, 12dB/oct</i>
<i>V on Speaker</i>	<i>9 V</i>
<i>Test duration</i>	<i>2 hours</i>

MECHANICAL & SHIPPING INFORMATIONS

Net weight	0,55 kg
Overall Diameter	90 mm
Overall Depth	35 mm
Mounting holes number	4
Mounting holes diameter	4,3 mm
Mounting bolt diameter	73,5 mm

MATERIALS

Flange	Aluminium
Voice Coil Former Material	Nomex®
Voice Coil Wire	Copper
Membrane Material	Aluminium
Membrane Shape	Waves
Suspension Material	Aluminium
Suspension Shape	Flat
Magnet Type	Neodymium
Magnet Weight	165 g

DIAGRAM

Frequency Response	Free air - 1m - 2,83 V
Impedance	(Iac=10m A)