

KEY FEATURES

- 40 Watt Max Power
- 26 mm (1 in) voice coil, copper wire
- Aluminium diaphragm



GENERAL SPECIFICATIONS

Throat Diameter	1 in - 25 mm
Nominal Impedance	8 Ohm
Power handling (AES) (*)	20 Watt
Max Power	40 Watt
Minimum Impedance	6,5 Ohm
Frequency Range	5-20 kHz
Voice coil resistance	5,8 Ohm
Voice Coil Diameter	1 in - 26 mm
S.P.L. (1w, 1m)	105 dB
Nominal Fs	2200 Hz
Flux Density	1,6 T
Crossover Frequency	2 kHz

MECHANICAL & SHIPPING INFORMATIONS

Net weight	1,15 kg
Overall Diameter	130 mm
Overall Depth	44 mm
Mounting holes number	4
Mounting holes diameter	5 mm
Mounting bolt diameter	116 mm

MATERIALS

Flange	Aluminium
Voice Coil Former Material	Polyamide
Voice Coil Wire	Copper
Membrane Material	Aluminium
Membrane Shape	Waves
Suspension Material	Aluminium
Suspension Shape	Flat
Magnet Type	Ferrite
Magnet Weight	355 g

DIAGRAM

Frequency Response	Baffle 30x48 cm - 1m - 2,83 V
Impedance	(Iac=10m A)

