

KEY FEATURES

- 40 Watt Max Power
- 38 mm (1,5 in) voice coil, aluminium wire
- Doped fabric diaphragm



GENERAL SPECIFICATIONS

Throat Diameter	1,5 in - 38 mm
Nominal Impedance	8 Ohm
Power handling (AES) (*)	20 Watt
Max Power	40 Watt
Minimum Impedance	5,5 Ohm
Frequency Range	1-18 kHz
Voice coil resistance	5,8 Ohm
Voice Coil Diameter	1,5 in - 38 mm
S.P.L. (1w, 1m)	98 dB
Nominal Fs	1000 Hz
Flux Density	1 T
Crossover Frequency	1 kHz

MECHANICAL & SHIPPING INFORMATIONS

Net weight	1,1 kg
Overall Diameter	114 mm
Overall Depth	70 mm
Mounting holes number	3
Mounting holes diameter	5 mm
Mounting bolt diameter	103 mm

MATERIALS

Pot Material/Flange	Plastic
Voice Coil Former Material	Kapton
Voice Coil Wire	Aluminium
Membrane Material	Doped Fabric
Membrane Shape	Dome
Suspension Material	Doped Fabric
Suspension Shape	Flat
Magnet Type	Ferrite
Magnet Weight	335 g

DIAGRAM

Frequency Response	free air - 1m - 2,83 V
Impedance	(Iac=10mA)

